

Viscon® HF

High Flow Fluid Heaters

Improved production times

- Spiral passages provide three times the flow rate of existing Viscon heaters and increase the internal heated contact area
- Speeds preheating times for highly viscous materials – gets the job started faster

Customizable to your application needs

- Available in manual thermostat or externally controlled versions
- “Set and forget” digital temperature maintenance when used with external controls
- Inlet can be positioned to face front, back, sides or bottom of the unit
- Outlet can be positioned on left or right side of the unit
- Viscon HF can be mounted anywhere a Viscon HP currently fits, making it backwards compatible



Externally Controlled
Viscon HF Heater.
Non-explosive Atmosphere heater shown.



Complete Viscon HF Heater
with Manual Thermostat Control.
Explosive Atmosphere heater shown.

Excellent for high solids coatings

- Improves flow and reduces pressure drop
- Ideal for protective coating materials

Efficient and powerful

- Supports high production rates
- Fast warming cycle improves uptime
- 5400 watts of power

Heater maintenance has never been this easy

Because the Viscon HF is designed for easy cleaning, you can clear plugs and perform maintenance in-house – no need for service calls. The Viscon HF is easy to disassemble and has replaceable heat rods as well.



APPLICATIONS

- Fireproofing
- Marine and offshore corrosion protection
- Wind tower manufacturing
- Railcar manufacturing and repair
- Container manufacturing
- Structural steel coatings
- Tank and pipe coatings and linings
- Floor coatings
- Processing plants

MATERIALS

- High solids coatings
- Epoxy primers and coatings
- Epoxy intumescent coatings
- Urethane coatings
- Waterborne coatings
- Adhesives and sealants
- Paints and stains
- Lubricants
- Fireproofing

TECHNICAL SPECIFICATIONS

Maximum fluid working pressure	7250 psi (500 bar, 50 MPa)
Energy consumption	.5400 Watts (240 V, 1-ph)
Fluid passage heat transfer area	.210 in ² (1355 cm ²)
Fluid passage dimensions (3 parallel paths)	Height: 0.41 in (10 mm) Width: 0.32 in (8 mm) Length: 3 x 48 in (8 x 122 cm)
Fluid connections	3/4 npt (f) with adapters down to 1/2 npt (m)
Fluid passage equivalent diameter	.072 in (18 mm)
Thermometer range (Models 24P016 and 24W248)	64 – 250°F (18 - 121°C)
Wetted parts	Stainless Steel, Anodized Aluminum, Electroless Nickel-Plated Steel, PTFE
Temperature operating range	.84 - 219°F (29 - 104°C)
Weight (Non-explosive atmosphere heaters)	51 lb (23 kg)
Weight (Explosive atmosphere heaters)	.70 lb (32 kg)
RTD (Models 262853 and 24W612)	.1000 ohm, class B, 3-wire Connector: M8, 4-pin male
Instruction manual	3A2954

ORDERING INFORMATION

Series C

Thermostat controlled heaters. 240 VAC 1-ph, 5400 watts, 22.5 amps. Includes manual thermostat, over temperature cutout switch, temperature gauge and pilot light. Requires only a power source.

- 24P016** Viscon HF, thermostat controlled for non-explosive atmosphere locations
- 24W248** Viscon HF, thermostat controlled for explosive atmosphere locations

Externally controlled heaters. 240 VAC 1-ph, 5400 watts, 22.5 amps. Works with your digital control or some Graco products with embedded control. Includes outlet manifold, over temperature outlet switch, 1000-ohm RTD sensor and pilot light. Requires power source, external controller and power switching.

- 262853** Viscon HF, externally controlled for non-explosive atmosphere locations
- 24W612** Viscon HF, externally controlled for explosive atmosphere locations



Contact us today!

To receive product information or to request a hands-on demonstration, call 877-844-7226 or visit www.graco.com.

©2013-2015 Graco Inc. 348890B 07/15 All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.